

**REAR VIEW CAMERA for outside mounting****Feature:**

- Outside mounting
- 130° viewing angle
- Electronic Shutter Control (ESC)
- Mirror function



|                                  |   |
|----------------------------------|---|
| Sensor:                          | 1/3" SONY Super HAD CCD   |
| System:                          | PAL, 625 lines, 50 fields / s, 50 Hz (vertical) / 15,625 (horizontal) |
| Backlight compensation:          | Automatic   |
| Synchronizing system:            | Internal sync   |
| Sensitivity:                     | 0 lux (0,001 with activated IR LED)                                   |
| Horizontal resolution:           | 380 TVL   |
| Picture elements:                | Approx 290000   |
| S/N ratio:                       | >48 dB  |
| Electronic Shutter Control(ESC): | 1 / 60 til 1/100.000 sec., depending on the illumination              |
| Video output:                    | 1 Vpp, BAS, 75 Ω specifications                                       |
| Gamma korrektion:                | Approx 0,45   |
| Objektivt:                       | 2,5 mm  |
| Power voltage:                   | 12 V DC   |
| Power:                           | 2,5 W   |
| Dimensions:                      | 60 x 55 x 78,5 mm   |
| Operation temperature:           | -30° to +60°C   |
| Material:                        | Aluminum allory   |
| Color:                           | Silver  |
| Weight:                          | 280 gram  |
| Water proff:                     | IP67  |